

DESCRIPTION

A high quality water based, acrylic resin based coating formulated for interior and exterior use. Durable and slip resistant, it provides the ideal coating for all-weather hard court areas.

RECOMMENDED USES



All-weather hard courts and sporting areas.

SPECIAL PROPERTIES

Slip resistant. Interior and exterior use.

COLOUR RANGE

Red; Green.

FINISH

Matt.

VOLUME SOLID

35%

COVERAGE



Johnstone's Hard Court Paint will cover at the rate of approximately 5-7 square metres per litre when applied by brush or roller and approximately 9-10 square metres per litre when applied by airless spray depending on the nature and porosity of the surface being painted.

DRYING TIME



Touch dry in 2-3 hours.
Recoat after 4-6 hours.

TRANSPORTATION & STORAGE

To avoid the risk of spillage always store and transport in a secure upright position. PROTECT FROM FROST.

THINNER

Water.

VOC CONTENT

MINIMAL VOC CONTENT 0-0.29%

VOC's (Volatile Organic Compounds) contribute to atmospheric pollution.

EU limit value for this product (Cat A/I): 140g/l (2007) / 140g/l (2010).
This product contains max 3g/l VOC.

FILM THICKNESS

Wet: 95µm, dry: 33µm.

SIZE

10 Litre

PREPARATION

All surfaces to be coated should be clean, dry and free from loose and flaking material. Remove any mould, algae or lichen etc. and ensure the surface is level and adequately drained. On self-draining courts clear drainage channels before painting.

APPLICATION



Stir well. Easy to apply by brush or roller. Also suitable for application by spray. For best results apply by airless spray at a pressure of 2000 psi using 21-31 thou. tips. If more than one can of a colour is to be used in the same area, intermix before use. Do not apply in temperatures below 10°C or externally if rain is imminent.

CLEANING



Remove as much product as possible from application equipment before cleaning. Clean equipment immediately after use with warm soapy water and rinse thoroughly. Replace lid firmly. Some local authorities have special facilities for the disposal of waste coatings. Do not empty product into drains or watercourses.

PRECAUTIONS

- Ensure good ventilation during application and drying.
- Avoid contact with skin and eyes.
- In case of contact with eyes, rinse immediately with plenty of water and seek medical advice.
- After contact with skin, wash immediately with plenty of soap and water or a recognised skin cleaner.
- When spraying, do not breathe spray, wear suitable respiratory protective equipment.
- Keep out of the reach of children.

PROFESSIONAL DECORATORS

Safety data sheet available for professional user on request.

