

DESCRIPTION

Quick Dry Satin Woodstain has been specially formulated to protect and stain smooth planed hardwoods and softwoods. This water-based, quick drying, microporous formulation ensures that most tasks can be completed in one day.

AVAILABLE IN

750ml and 2.5 Litre.

COLOUR RANGE

Clear; Walnut; Pine; Antique Pine; Ebony; Jacobean Oak; Light Oak; Mahogany; Medium Oak; Rosewood; Teak and Redwood.

RECOMMENDED USES



Suitable for interior and exterior use.

TYPES OF SUBSTRATE

Doors, window frames, fascia boards, cladding, garden furniture.

COVERAGE



Approximately 12 square metres per litre depending on the nature and porosity of the surface being stained.

DRYING TIME



Touch dry in 1 hour.
Recoat after 4 hours.
Allow longer in adverse conditions.

TRANSPORTATION & STORAGE

To avoid the risk of spillage, always store and transport in a secure, upright position. PROTECT FROM FROST.

THINNER

Water.

VOC CONTENT

LOW VOC CONTENT 0.30–7.99%
VOC's (Volatile Organic Compounds) contribute to atmospheric pollution.

EU limit value for this product (Cat A/e): 150g/l (2007) / 130g/l (2010).
This product contains max 80g/l VOC.

PREPARATION

Ensure all surfaces to be stained are sound, clean, dry and free from dust, grease, polish or any other surface contaminant. Remove any resins and natural oils using White Spirit. Sound, existing varnish should be rubbed down with fine waterproof abrasive paper, rinsed thoroughly and allowed to dry. Do not prepare the surface using steel wool. Avoid the inhalation of dust. Wear a suitable face mask if dry sanding. Special precautions should be taken during surface preparation of pre-1960's paint surfaces over wood and metal as they may contain harmful lead.

APPLICATION



Stir Quick Dry Satin Woodstain thoroughly before use. Apply two or more coats of woodstain evenly, by brush along the grain paying particular attention to the end grain. Do not overlap the brush strokes. On bare or new wood the first coat can be thinned with up to 10% clean water, followed by two further coats of undiluted woodstain. Do not apply when temperature is below 10°C or when rain is imminent.

PLEASE NOTE: The final colour will depend on the original colour of the wood and the number of coats applied.

CLEANING



Remove as much product as possible from brushes before cleaning. Clean brushes immediately after use with warm soapy water and rinse thoroughly. Replace lid firmly. Some local authorities have special facilities for the disposal of waste coatings. Do not empty product into drains or watercourses.

PRECAUTIONS

- Ensure good ventilation during application and drying.
- Avoid contact with skin and eyes.
- In case of contact with eyes, rinse immediately with plenty of water and seek medical advice.
- After contact with skin, wash immediately with plenty of soap and water or a recognised skin cleaner.
- Keep out of the reach of children.

PROFESSIONAL DECORATORS

Safety data sheet available for professional user on request.

