

1.8 Acrylic Gloss



DESCRIPTION

A tough, self-undercoating, water-based gloss finish, manufactured from high opacity pigments and acrylic resin. Suitable for interior and exterior use on both wood and appropriately primed metal surfaces. Ideal for use where its excellent covering power and speed of drying enable the task to be completed quickly.

Recommended uses

Interior ✓ Exterior ✓

Type of substrate

Wood and metal.

Colour range

Brilliant White, Black and a range of ready mixed colours. Additional colours are available via the Leyland tinting system.

Finish

Gloss

Volume solid

37%

Coverage

1 litre will cover approximately 10 square metres, depending on the nature and porosity of the surface. Strong or contrasting colours may require additional coats. Under normal conditions, touch dry in 2 hours and recoatable after 6 hours. Conditions of low temperature or high humidity can prolong the drying time.

Drying time

Touch dry in 2 hours. Recoatable after 6 hours.

Transportation and storage

To avoid the risk of spillage, always store and transport in a secure upright position.
PROTECT FROM FROST.

Thinner

Clean water.

VOC content

MEDIUM VOC CONTENT 8-24.99%
VOCs (Volatile Organic Compounds) contribute to atmospheric pollution.

EU limit value for this product (Cat A/d): 150 g/l (2007) / 130 g/l (2010). This product contains max 130 g/l VOC.

Film thickness

Wet: 100µm
Dry: 37µm

Preparation

Ensure surface to be painted is sound, clean, dry and free from grease. Remove all loose and defective paint. Rub down previously painted surfaces with fine waterproof abrasive paper and rinse thoroughly before applying a pre-coat of Acrylic Primer Undercoat. Avoid the inhalation of dust. Wear a suitable face mask if dry sanding. Prime where required with appropriate Leyland Primer. Special precautions should be taken during surface preparation of pre-1960s paint surfaces over wood and metal as they may contain harmful lead. For further advice contact Technical Advisory.

Application

Do not stir. For best results use a synthetic or good quality bristle brush, fully load the brush and apply liberally and evenly. Avoid overspreading. Do not apply where air or surface temperatures are below 10°C or externally when rain is imminent.

Cleaning

Remove as much product as possible from application equipment before cleaning. Clean equipment immediately after use in warm, soapy water and rinse thoroughly. Some local authorities have special facilities for disposal of waste coatings. Do not empty product into drains or watercourses. Replace lid firmly.

Precautions

PAINT PRODUCT

- Ensure good ventilation during application and drying.
- Avoid contact with skin and eyes.
- In case of contact with eyes, rinse immediately with plenty of water and seek medical advice.
- After contact with skin, wash immediately with plenty of soap and water or a recognised skin cleaner.
- Keep out of the reach of children.

PROFESSIONAL DECORATORS Safety data sheet available on request.
Manufactured under a quality system approved by the BSI.