

## 1.16 Alkali Resisting Wall Primer



### DESCRIPTION

A solvent-based alkali-resisting primer and sealer for interior and exterior masonry surfaces. Resists alkali attack and promotes first class adhesion. Also suitable for use on other surfaces including wood and fibreglass. Ideal for use under both oil-based and water-borne paints.

### Recommended uses

Interior ✓ Exterior ✓

### Type of substrate

Plaster, concrete, cement rendering, brick, stone and blockwork.

### Colour range

White.

### Finish

N/A

### Volume solid

57%

### Coverage

1 litre will cover approximately 10 square metres depending on the nature and porosity of the surface.

### Drying time

Touch dry in 4-6 hours. Recoatable after 16-24 hours.

### Transportation and storage

To avoid the risk of spillage, always store and transport in a secure upright position.  
STORE AWAY FROM HEAT AND FLAME.

### Cleaner

White Spirit.

### VOC content

HIGH VOC CONTENT 25-50%  
VOCs (Volatile Organic Compounds) contribute to atmospheric pollution.

EU limit value for this product (Cat A/g): 450 g/l (2007) / 350 g/l (2010). This product contains max 350 g/l VOC.

### Film thickness

Wet: 50µm  
Dry: 28µm

### Preparation

Ensure surface to be painted is sound, clean, dry and free from grease. Hard wall plasters should be scored with coarse glasspaper. Avoid the inhalation of dust. Wear a suitable face mask if dry sanding. Special precautions should be taken during surface preparation of pre-1960s paint surfaces over wood and metal as they may contain harmful lead. For further advice contact Technical Advisory.

### Application

Stir well before use. Suitable for application by brush or roller. Best results are obtained by brush application as this ensures better penetration into the surface. Apply one full coat brushing firmly into the surface. Allow 16-24 hours to dry under normal conditions, before following with the selected paint finish.

### Cleaning

Remove as much product as possible from application equipment before cleaning. Clean equipment immediately after use with White Spirit or Turpentine Substitute. Some local authorities have special facilities for disposal of waste coatings. Do not empty product into drains or watercourses. Replace lid firmly.

### Precautions

PAINT PRODUCT  
FLAMMABLE

- Contains Ethyl Methyl Ketoxime. May produce an allergic reaction.
- Repeated exposure may cause skin dryness or cracking.
- Keep away from sources of ignition – No smoking.
- Ensure maximum ventilation during application and drying.
- Avoid contact with skin and eyes. In case of contact with eyes rinse immediately with plenty of water and seek medical advice.
- After contact with skin, wash immediately with plenty of soap and water or a recognised skin cleaner – DO NOT USE SOLVENT OR THINNERS.
- When applying by brush or roller to large interior surfaces or in confined spaces, wear a suitable cartridge respirator or airfed respiratory protective equipment.
- If swallowed, seek medical advice immediately and show this container or label.
- Keep out of the reach of children.

PROFESSIONAL DECORATORS Safety data sheet available on request.  
Manufactured under a quality system approved by the BSI.