

2.1 Contract Matt



DESCRIPTION

Leyland Contract Matt is specially formulated to provide a full bodied, high opacity, matt finish to all interior walls and ceilings making it ideal for new work application.

Recommended uses

Interior ✓ Exterior ✗

Type of substrate

Plaster and embossed wallcoverings. Also suitable for use on wallboards, concrete, brickwork and blockwork.

Colour range

Brilliant White and Magnolia.

Finish

Matt

Volume solid

24%

Coverage

Leyland Contract Matt will cover approximately 13 square metres per litre depending on the nature and porosity of the surface. When using more than one tin of a colour in the same room, intermix before use.

Drying time

Touch dry in 1-2 hours. Recoatable after 2-4 hours.

Transportation and storage

To avoid the risk of spillage, always store and transport in a secure upright position.
PROTECT FROM FROST.

Thinner

Clean water.

VOC content

LOW VOC CONTENT 0.30-7.99%

VOCs (Volatile Organic Compounds) contribute to atmospheric pollution.

EU limit value for this product (Cat A/a): 75 g/l (2007) / 30 g/l (2010). This product contains max 15 g/l VOC.

Film thickness

Wet: 90µm
Dry: 22µm

Preparation

All surfaces to be painted should be clean, dry and free from loose and flaking material. Avoid the inhalation of dust. Wear a suitable face mask if dry sanding. Seal absorbent surfaces with a solution of up to 1 part water to 9 parts Leyland Contract Matt.

Application

Stir well before use. Do not thin, except for absorbent surfaces, or when applying by roller or spray when a small quantity of clean water may be added. Suitable for application by brush, roller or spray. Apply paint evenly by brush or roller and avoid overspreading. If required, a second coat may be applied after 2 to 4 hours. Do not apply in temperatures below 10°C.

Cleaning

Remove as much product as possible from application equipment before washing. Replace lid firmly. Wash equipment immediately after use with warm soapy water. Some local authorities have special facilities for the disposal of waste coatings. Do not empty product into drains or watercourses.

Precautions

PAINT PRODUCT

- Ensure good ventilation during application and drying.
- Avoid contact with skin and eyes.
- In case of contact with eyes, rinse immediately with plenty of clean water and seek medical advice.
- After contact with skin, wash immediately with plenty of soap and water or a recognised skin cleaner.
- When spraying, do not breathe spray, wear suitable respiratory protective equipment.
- Keep out of the reach of children.