

Fast Drying Water Based Satin



DESCRIPTION

Leyland Fast Drying Satin is a premium quality, high opacity paint specially developed to produce a tough satin sheen finish that dries quickly. Suitable for interior and exterior wood and metal, the non yellowing formula benefits from excellent flow and is both fast drying and low odour ensuring easy application and minimal downtime.

Recommended uses

Interior ✓ Exterior ✓

Type of substrate

Wood and metal.

Colour range

Brilliant White, Black and thousands of additional colours are available via the Leyland tinting system.

Finish

Satin

Volume solid

35%

Coverage

1 litre will cover approximately 12 square metres, depending on the nature and porosity of the surface. Strong or contrasting colours may require additional coats. When using more than one can of a colour in the same room, intermix before use.

Drying time

Recoat after 4 hours.

Transportation and storage

To avoid the risk of spillage, always store and transport in a secure upright position.
PROTECT FROM FROST.

Thinner

Clean water.

VOC content

LOW VOC CONTENT 0.3-7.99%
VOCs (Volatile Organic Compounds) contribute to atmospheric pollution.

EU limit value for this product (Cat A/d): 130 g/l (2010).
This product contains max 80 g/l

Film thickness

Wet: 80µm
Dry: 28µm

Preparation

Ensure surface to be painted is sound, clean, dry and free from grease. Rub down sound previously gloss painted surfaces with fine waterproof abrasive paper to provide a key and rinse thoroughly before applying a pre-coat of Leyland Trade Fast Drying Undercoat. Avoid the inhalation of dust. Wear a suitable face mask if dry sanding. Apply Knotting Solution to knots and resinous surfaces and prime exposed wood and metal surfaces with the appropriate Leyland Primer. For further advice contact Technical Advisory. Allow radiators to cool before painting.

Application

Stir well before use. Apply by brush or roller. Apply liberally and evenly for a smooth finish. Under normal conditions, allow 4 hours before applying a second coat if required. Do not apply when air or surface temperature is below 10°C or externally when rain is imminent.

Cleaning

Remove as much product as possible from application equipment before cleaning. Clean immediately after use in warm soapy water and rinse thoroughly. Replace lid firmly. Some local authorities have special facilities for the disposal of waste coatings. Do not empty product into drains or watercourses.

Precautions

PAINT PRODUCT

- Ensure good ventilation during application and drying.
- Avoid contact with skin and eyes.
- In case of contact with eyes, rinse immediately with plenty of water and seek medical advice.
- After contact with skin, wash immediately with plenty of soap and water or a recognised skin cleaner.
- When spraying do not breathe spray, wear suitable respiratory protective equipment.
- Keep out of the reach of children.

PROFESSIONAL DECORATORS Safety data sheet available on request.
Manufactured under a quality system approved by the BSI.