

## Fast Drying Water Based Undercoat



### DESCRIPTION

Leyland Fast Drying Undercoat has been specially developed to work with Leyland Trade Fast Drying High Gloss. A quick drying, high performance undercoat for interior and exterior suitably primed metal and a combined primer and undercoat for interior and exterior wood. The non yellowing formula benefits from excellent flow and is both fast drying and low odour ensuring easy application and minimal downtime.

### Recommended uses

Interior ✓ Exterior ✓

### Type of substrate

Wood, Metal, plaster, concrete, cement rendering, brickwork and blockwork.

### Colour range

Brilliant White, Dark Grey and thousands of additional colours are available via the Leyland tinting system.

### Finish

Non applicable

### Volume solid

36%

### Coverage

1 litre will cover approximately 13 square metres, depending on the nature and porosity of the surface. Strong or contrasting colours may require additional coats.

### Drying time

Recoat after 1-2 hours.

### Transportation and storage

To avoid the risk of spillage, always store and transport in a secure upright position.  
PROTECT FROM FROST.

### Thinner

Clean water.

### VOC content

LOW VOC CONTENT 0.3-7.99%

VOCs (Volatile Organic Compounds) contribute to atmospheric pollution.

EU limit value for this product (Cat A/d): 130 g/l (2010).  
This product contains max 15 g/l

**PROFESSIONAL DECORATORS Safety data sheet available on request.**  
Manufactured under a quality system approved by the BSI.

### Film thickness

Wet: 77µm  
Dry: 27µm

### Preparation

Ensure surface to be painted is sound, clean, dry and free from grease. Rub down bare timber surfaces with fine waterproof abrasive paper to remove raised grain and sharp edges. Apply Knotting Solution to knots and resinous surfaces. Rub down sound previously gloss painted surfaces with fine waterproof abrasive paper to provide a key. Avoid the inhalation of dust. Wear a suitable face mask if dry sanding. Prime where required with the appropriate Leyland Primer. For further advice contact Technical Advisory. Allow radiators to cool before painting.

### Application

Stir well before use. Apply by brush or roller. Apply liberally, brushing firmly into the surface. Treat all accessible timber, in particular the end grain. Allow 1-2 hours before applying a second coat if required. Conditions of low temperature or high humidity can prolong the drying time. Do not apply when air or surface temperature is below 10°C or externally when rain is imminent.

### Cleaning

Remove as much product as possible from application equipment before cleaning. Clean equipment immediately after use in warm soapy water and rinse thoroughly. Replace lid firmly. Some local authorities have special facilities for disposal of waste coatings. Do not empty product into drains or watercourses.

### Precautions

PAINT PRODUCT

- Ensure good ventilation during application and drying.
- Avoid contact with skin and eyes.
- In case of contact with eyes, rinse immediately with plenty of water and seek medical advice.
- After contact with skin, wash immediately with plenty of soap and water or a recognised skin cleaner.
- When spraying do not breathe spray, wear suitable respiratory protective equipment.
- Keep out of the reach of children.